


NEW OR EXISTING  
LIGHT REQUIRED



OPEN GUARDRAILS AND OPEN HANDRAILS ON DECKS AND STAIRWAYS MORE THAN 30 INCHES ABOVE GRADE OR A FLOOR BELOW SHALL HAVE MEMBERS SPACED SO THAT A 4" DIAMETER SPHERE CANNOT PASS THROUGH

- STAIRWAY NOTES:**
1. STAIRWAYS SHALL BE NOT LESS THAN 36" IN WIDTH
  2. STAIRWAY RISES SHALL BE NOT GREATER THAN 8 1/4"
  3. STAIRWAY TREADS SHALL HAVE MIN. RUN OF 9"
  4. THE LENGTH OF RUN AND THE HEIGHT OF RISER SHALL NOT VARY MORE THAN 3/8" IN THE ENTIRE RUN OF THE STAIR
  5. STAIRS ARE REQUIRED TO BE ILLUMINATED
  6. OPEN RISERS PERMITTED IF OPENING IS LESS THAN 4"
  7. MINIMUM 3/4" NOSING

- HANDRAIL NOTES:**
1. HANDRAILS TO BE CONTINUOUS ON ONE SIDE OF STAIRS WITH FOUR OR MORE RISERS
  2. HANDRAILS PLACED 34-38" ABOVE STAIR NOSING

